

4 Combination table

4 - 1 Combination Table

2MXM68N

Cooling ·(50Hz 230V)·

Outdoor unit	Indoor unit	Cooling capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
2MXM68N2V1B	1,5	1,60	---	1,52	1,60	2,49	0,40	0,42	0,59	1,82	1,98	2,71	95
	2,0	2,00	---	1,66	2,00	2,68	0,42	0,43	0,60	1,91	2,08	2,75	95
	2,5	2,50	---	1,74	2,50	3,44	0,44	0,55	0,82	2,00	2,62	3,77	95
	3,5	3,50	---	1,93	3,50	4,86	0,46	0,80	1,43	2,09	3,84	6,53	95
	4,2	---	4,20	1,93	4,20	5,33	0,46	0,82	1,44	2,09	3,93	6,57	95
	5,0	---	5,00	1,94	5,00	6,03	0,44	1,50	2,13	2,00	7,20	9,77	95
	6,0	---	6,00	1,94	6,00	6,51	0,44	1,52	2,13	2,00	7,29	9,77	95
	1.5+1.5	1,50	1,50	1,95	3,00	4,79	0,40	0,60	1,15	1,81	2,75	5,25	95
	1.5+2.0	1,50	2,00	1,95	3,50	4,96	0,40	0,74	1,22	1,81	3,38	5,58	95
	1.5+2.5	1,50	2,50	1,95	4,00	5,28	0,40	0,89	1,36	1,81	4,08	6,23	95
	1.5+3.5	1,50	3,50	1,95	5,00	6,17	0,39	1,24	1,83	1,77	5,68	8,39	95
	1.5+4.2	1,50	4,20	1,95	5,70	6,39	0,39	1,51	1,96	1,77	6,90	8,96	95
	1.5+5.0	1,50	5,00	1,95	6,50	7,08	0,38	1,78	2,23	1,73	8,14	10,22	95
	1.5+6.0	1,36	5,44	1,96	6,80	7,59	0,37	1,93	2,36	1,68	8,82	10,79	95
	2.0+2.0	2,00	2,00	1,95	4,00	5,12	0,40	0,89	1,29	1,81	4,08	5,91	95
	2.0+2.5	2,00	2,50	1,95	4,50	5,44	0,40	1,06	1,43	1,81	4,86	6,56	95
	2.0+3.5	2,00	3,50	1,95	5,50	6,30	0,39	1,39	1,91	1,77	6,38	8,76	95
	2.0+4.2	2,00	4,20	1,95	6,20	6,51	0,39	1,70	2,05	1,77	7,77	9,37	95
	2.0+5.0	1,94	4,86	1,95	6,80	7,26	0,38	1,90	2,36	1,73	8,68	10,79	95
	2.0+6.0	1,70	5,10	1,96	6,80	7,71	0,37	1,92	2,45	1,68	8,78	11,20	95
	2.5+2.5	2,50	2,50	1,95	5,00	6,10	0,41	1,20	1,78	1,89	5,51	8,15	95
	2.5+3.5	2,50	3,50	1,95	6,00	6,57	0,40	1,54	2,11	1,81	7,03	9,65	95
	2.5+4.2	2,50	4,20	1,95	6,70	6,95	0,40	1,79	2,38	1,81	8,21	10,88	95
	2.5+5.0	2,27	4,53	1,95	6,80	7,37	0,37	1,78	2,45	1,68	8,15	11,20	95
	2.5+6.0	2,00	4,80	1,96	6,80	7,71	0,35	1,76	2,45	1,60	8,06	11,20	95
	3.5+3.5	3,40	3,40	1,95	6,80	7,13	0,38	1,73	2,37	1,73	7,90	10,83	95
	3.5+4.2	3,09	3,71	1,95	6,80	7,24	0,38	1,72	2,46	1,73	7,87	11,24	95
	3.5+5.0	2,80	4,00	1,95	6,80	7,76	0,35	1,68	2,78	1,60	7,71	12,71	95
	3.5+6.0	2,51	4,29	2,26	6,80	8,07	0,40	1,67	2,72	1,81	7,63	12,46	95
	4.2+4.2*	3,40	3,40	1,95	6,80	7,14	0,38	1,71	2,37	1,73	7,84	10,83	95
	4.2+5.0*	3,10	3,70	1,95	6,80	7,77	0,35	1,68	2,78	1,60	7,68	12,71	95
	4.2+6.0*	2,80	4,00	2,26	6,80	8,08	0,40	1,66	2,72	1,81	7,60	12,46	95

Notes

- The total capacity of each connected indoor unit is up to ·10.2·kW.
- The values above are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0· kW class
Wall-mounted ·CTXM-M, CTXM-N, CTXM-R, FTXM-M, FTXM-N, FTXM-R· series
* Only for ·CTXM-R and FTXM-R series·
- Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB

3D131347

2MXM68N

Heating ·(50Hz 230V)·

Outdoor unit	Indoor unit	Heating capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room -A-	Room -B-	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2MXM68N2V1B	1,5	2,70	---	1,47	2,70	4,08	0,42	0,72	1,22	1,91	3,35	5,59	95
	2,0	2,72	---	1,48	2,72	4,09	0,43	0,73	1,28	1,95	3,39	5,64	95
	2,5	3,40	---	1,44	3,40	4,30	0,42	1,02	1,37	1,91	4,72	6,08	95
	3,5	4,30	---	1,45	4,30	4,90	0,40	1,41	1,75	1,82	6,50	7,15	95
	4,2	---	4,32	1,44	4,32	5,70	0,40	1,40	2,04	1,82	6,46	7,15	95
	5,0	---	5,60	1,66	5,60	6,90	0,39	1,82	2,59	1,78	8,43	8,70	95
	6,0	---	7,90	1,88	7,90	8,91	0,37	2,62	2,64	1,69	12,13	12,08	95
	1,5+1,5	2,65	2,65	1,65	5,30	7,38	0,36	1,19	1,83	1,63	5,45	8,38	95
	1,5+2,0	2,44	3,26	1,65	5,70	7,76	0,36	1,31	1,99	1,63	6,00	9,09	95
	1,5+2,5	2,29	3,81	1,65	6,10	7,95	0,36	1,43	2,06	1,63	6,55	9,43	95
	1,5+3,5	2,07	4,83	1,80	6,90	8,50	0,37	1,69	2,35	1,68	7,74	10,74	95
	1,5+4,2	1,97	5,53	1,80	7,50	8,85	0,37	1,90	2,57	1,68	8,70	11,75	95
	1,5+5,0	1,89	6,31	2,18	8,20	10,38	0,45	2,13	2,91	2,06	9,75	13,31	95
	1,5+6,0	1,72	6,88	2,46	8,60	10,58	0,48	2,28	2,67	2,19	10,44	12,21	95
	2,0+2,0	3,25	3,25	1,65	6,50	7,95	0,36	1,37	2,31	1,63	6,28	9,47	95
	2,0+2,5	3,07	3,83	1,65	6,90	8,12	0,36	1,52	2,32	1,63	6,96	9,81	95
	2,0+3,5	2,73	4,77	1,80	7,50	8,67	0,37	1,75	2,43	1,68	8,01	11,12	95
	2,0+4,2	2,58	5,42	1,80	8,00	9,03	0,37	1,98	2,66	1,68	9,07	12,17	95
	2,0+5,0	2,46	6,14	2,18	8,60	10,56	0,45	2,26	3,00	2,06	10,35	13,73	95
	2,0+6,0	2,15	6,45	2,46	8,60	10,75	0,48	2,24	2,74	2,19	10,26	12,55	95
	2,5+2,5	3,60	3,60	1,65	7,20	8,49	0,36	1,62	2,36	1,63	7,42	10,78	95
	2,5+3,5	3,29	4,61	1,89	7,90	9,03	0,38	1,91	2,66	1,72	8,75	12,17	95
	2,5+4,2	3,10	5,20	1,89	8,30	9,29	0,38	2,11	2,82	1,72	9,66	12,93	95
	2,5+5,0	2,87	5,73	2,27	8,60	10,68	0,46	2,24	3,09	2,11	10,26	14,15	95
	2,5+6,0	2,53	6,07	2,55	8,60	10,88	0,50	2,22	2,77	2,28	10,17	12,67	95
	3,5+3,5	4,30	4,30	2,17	8,60	9,38	0,42	2,26	2,86	1,94	10,35	13,09	95
	3,5+4,2	3,91	4,69	2,17	8,60	9,47	0,42	2,26	2,91	1,94	10,35	13,31	95
	3,5+5,0	3,54	5,06	2,56	8,60	10,90	0,51	2,22	3,13	2,32	10,17	14,32	95
	3,5+6,0	3,17	5,43	2,74	8,60	11,01	0,52	2,21	2,76	2,37	10,12	12,63	95
	4,2+4,2*	4,30	4,30	2,17	8,60	9,56	0,42	2,22	2,94	1,94	10,17	13,47	95
	4,2+5,0*	3,93	4,67	2,56	8,60	10,91	0,51	2,21	3,19	2,32	10,12	14,61	95
	4,2+6,0*	3,54	5,06	2,74	8,60	11,02	0,51	2,20	2,79	2,32	10,07	12,76	95

Notes

- The total capacity of each connected indoor unit is up to ·10.2·kW.
- The values above are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0· kW class
Wall-mounted ·CTXM-M, CTXM-N, CTXM-R, FTXM-M, FTXM-N, FTXM-R· series
* Only for ·CTXM-R and FTXM-R series·
- Heating capacity conditions
Indoor temperature ·20·°C DB
Outdoor temperature ·7·°C DB / ·6·°C WB
- Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB

3D131349