

4. Combination Table

4-1 AJ040TXJ2KG/EU

COOLING

Outdoor unit		A	B	Cooling Capacity		Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
				W		W			W			A						
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class		kWh
AJ040TXJ2KG	2 Unit	7	7	2000	2000	1300	4000	4700	300	900	1250	1.7	4.1	5.7	4.44	A+++	8.54	164
		7	9	1780	2220	1300	4000	4700	350	920	1270	1.9	4.2	5.8	4.35	A+++	8.51	165
		7	12	1450	2550	1300	4000	4700	350	930	1280	1.9	4.3	5.9	4.3	A+++	8.51	165
		9	9	2000	2000	1300	4000	4700	350	940	1290	1.9	4.3	5.9	4.26	A+++	8.51	165
		9	12	1670	2330	1300	4000	4700	350	950	1300	1.9	4.3	5.9	4.21	A+++	8.51	165

HEATING

Outdoor unit		A	B	Heating Capacity		Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
				W		W			W			A							
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	COP	Class		kW	kWh
AJ040TXJ2KG	2 Unit	7	7	2100	2100	1000	4200	4700	280	900	1180	1.4	4.1	5.4	4.67	A++	4.64	3.05	922
		7	9	1840	2360	1000	4200	4700	280	920	1190	1.4	4.2	5.4	4.57	A++	4.61	3.05	927
		7	12	1550	2650	1000	4200	4700	280	930	1200	1.4	4.3	5.5	4.52	A++	4.61	3.05	927
		9	9	2100	2100	1000	4200	4700	280	940	1210	1.4	4.3	5.5	4.47	A++	4.61	3.05	927
		9	12	1800	2400	1000	4200	4700	280	950	1220	1.4	4.3	5.6	4.42	A++	4.61	3.05	927

NOTE

- 1 EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- 2 The above is the value for connecting with the following indoor units.
 - Wind Free(PRM) : AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK
- 3 You can not connect a single unit.
- 4 Power consumption include indoor unit power.

4. Combination Table

4-2 AJ050TXJ2KG/EU

COOLING

Outdoor unit		A	B	Cooling Capacity		Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
				W		W			W			A						kWh
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class		
AJ050TXJ2KG	2 Unit	7	7	2000	2000	1300	4000	4700	350	980	1290	1.9	4.5	5.9	4.08	A+++	8.51	165
		7	9	2040	2560	1300	4600	5200	350	1120	1520	1.9	5.1	7	4.11	A+++	8.51	189
		7	12	1820	3180	1400	5000	5500	350	1230	1510	1.9	5.6	6.9	4.07	A+++	8.51	206
		7	18	1430	3570	1400	5000	5500	350	1200	1510	1.9	5.5	6.9	4.15	A+++	8.51	206
		9	9	2500	2500	1400	5000	5500	350	1220	1500	1.9	5.6	6.9	4.1	A+++	8.54	205
		9	12	2080	2920	1400	5000	5500	350	1230	1510	1.9	5.6	6.9	4.07	A+++	8.51	206
		9	18	1670	3330	1400	5000	5500	350	1230	1510	1.9	5.5	6.9	4.15	A+++	8.51	206
		12	12	2500	2500	1400	5000	5500	350	1240	1520	1.9	5.7	7	4.03	A+++	8.51	206
		12	18	2060	2940	1400	5000	5500	350	1240	1520	1.9	5.6	7	4.15	A+++	8.51	206

HEATING

Outdoor unit		A	B	Heating Capacity		Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
				W		W			W			A							
				A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				COP	Class
AJ040TXJ2KG	2 Unit	7	7	2200	2200	1400	4400	4700	280	1010	1210	1.4	4.6	5.5	4.36	A++	4.61	3.05	927
		7	9	2040	3060	1400	5100	5460	280	1310	1610	1.4	6	7.4	3.89	A++	4.61	4.21	1277
		7	12	2020	3680	1400	5600	6300	280	1290	1710	1.4	5.9	7.8	4.34	A++	4.61	4.21	1277
		7	18	1530	4170	1400	5600	6300	280	1270	1710	1.4	5.7	7.8	4.41	A++	4.61	4.07	1237
		9	9	2850	2850	1400	5600	6300	280	1280	1700	1.4	5.9	7.8	4.38	A++	4.64	4.21	1270
		9	12	2580	3120	1400	5600	6300	280	1290	1710	1.4	5.9	7.8	4.34	A++	4.61	4.21	1277
		9	18	2020	3680	1400	5600	6300	280	1270	1710	1.4	5.7	7.8	4.41	A++	4.61	4.07	1237
		12	12	2850	2850	1400	5600	6300	280	1300	1720	1.4	5.9	7.9	4.31	A++	4.61	4.21	1277
		12	18	2280	3420	1400	5600	6300	280	1280	1720	1.4	5.8	7.9	4.38	A++	4.61	4.07	1237

NOTE

- 1 EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- 2 The above is the value for connecting with the following indoor units.
 - Wind Free(PRM) : AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK
- 3 You can not connect a single unit.
- 4 Power consumption include indoor unit power.

4. Combination Table

4-3 AJ052TXJ3KG/EU

COOLING

Outdoor unit		A	B	C	Cooling Capacity			Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
					W			W			W			A						
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	EER	Class		
AJ052TXJ3KG	2 Unit	7	7		2000	2000		1100	4000	4800	320	1020	1630	2	4.5	7.5	3.92	A++	8.08	173
		7	9		2040	2560		1100	4600	5520	320	1170	1850	2	5.2	8.5	3.93	A++	7.73	208
		7	12		1820	3180		1100	5000	6290	320	1260	2000	2	5.6	9.2	3.97	A++	8.15	215
		7	18		1490	3710		1200	5200	6600	320	1300	2040	2	5.7	9.3	4.00	A++	7.85	232
		9	9		2500	2500		1100	5000	5800	320	1160	1980	2	5.1	9.1	4.30	A+++	8.51	206
		9	12		2080	2920		1100	5000	6400	320	1250	2020	2	5.5	9.2	4.00	A++	8.16	214
		9	18		1730	3470		1200	5200	6800	320	1300	2070	2	5.7	9.5	4.00	A++	7.85	232
		12	12		2600	2600		1100	5200	6560	320	1300	2040	2	5.7	9.3	4.00	A++	8.16	214
	3 Unit	7	7	7	1730	1730	1740	1450	5200	6380	330	1280	2020	2	5.7	9.2	4.06	A++	7.68	237
		7	7	9	1600	1600	2000	1450	5200	6490	330	1290	2040	2	5.7	9.3	4.03	A++	7.67	237
		7	7	12	1390	1390	2420	1450	5200	6800	330	1270	2070	2	5.6	9.5	4.09	A++	7.69	237
		7	9	9	1480	1860	1860	1450	5200	6600	330	1260	2040	2	5.6	9.3	4.13	A++	7.7	236
		7	9	12	1300	1630	2270	1450	5200	6800	330	1270	2070	2	5.6	9.5	4.11	A++	7.69	237
		9	9	9	1730	1730	1740	1450	5200	6800	330	1250	2070	2	5.5	9.5	4.16	A++	7.7	236
		9	9	12	1530	1530	2140	1450	5200	6800	330	1250	2070	2	5.5	9.5	4.16	A++	8.08	225

HEATING

Outdoor unit		A	B	C	Heating Capacity			Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
					W			W			W			A							
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	COP	Class		kW	kWh
AJ052TXJ3KG	2 Unit	7	7		2200	2200		950	4400	5060	280	1150	1510	1.7	5.4	6.9	3.83	A+	4.40	3.05	970
		7	9		2040	3060		950	5100	5870	280	1320	1830	1.7	6.1	8.4	3.86	A+	4.35	4.21	1352
		7	12		1990	3610		950	5600	6440	280	1450	1860	1.7	6.7	8.5	3.86	A+	4.34	4.60	1484
		7	18		1610	4390		950	6000	6900	280	1570	1860	1.7	7.2	8.5	3.82	A+	4.27	4.28	1401
		9	9		2900	2900		950	5800	6300	280	1510	1910	1.7	6.9	8.7	3.84	A++	4.60	4.60	1400
		9	12		2620	3180		950	5800	6300	280	1510	1910	1.7	6.9	8.7	3.84	A+	4.34	4.60	1484
		9	18		2240	4060		950	6300	7300	280	1640	1830	1.7	7.5	8.4	3.84	A+	4.27	4.28	1401
		12	12		2950	2950		950	5900	6880	280	1530	1860	1.7	7.0	8.5	3.86	A+	4.34	4.60	1484
	3 Unit	7	7	7	1930	1930	1940	1000	5800	6760	280	1500	1840	1.7	6.9	8.4	3.87	A+	4.30	4.60	1497
		7	7	9	1690	1690	2520	1000	5900	6840	280	1550	1840	1.7	7.1	8.4	3.81	A+	4.30	4.60	1497
		7	7	12	1650	1650	3000	1000	6300	7300	280	1560	1830	1.7	7.1	8.4	4.04	A+	4.30	4.60	1497
		7	9	9	1500	2250	2250	1000	6000	6920	280	1500	1840	1.7	6.9	8.4	4.00	A+	4.30	4.60	1497
		7	9	12	1460	2190	2650	1000	6300	7300	280	1530	1830	1.7	7.0	8.4	4.12	A+	4.30	4.60	1497
		9	9	9	2100	2100	2100	1000	6300	7300	280	1320	1830	1.7	6.1	8.4	4.77	A+	4.30	4.60	1497
		9	9	12	1850	1850	2600	1000	6300	7300	280	1320	1830	1.7	6.1	8.4	4.77	A+	4.30	4.60	1497



NOTE

- 1 EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- 2 The above is the value for connecting with the following indoor units.
 - Wind Free(PRM) : AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK
- 3 You can not connect a single unit.
- 4 Power consumption include indoor unit power.

4. Combination Table

4-4 AJ068TXJ3KG/EU

COOLING

Outdoor unit		A	B	C	Cooling Capacity			Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
					W			W			W			A						
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				EER
AJ068TXJ3KG/EU	2 Unit	7	7		2000	2000		1300	4000	4800	420	1110	1480	2.3	5.2	6.8	3.60	A++	7.55	185
		7	9		2000	2500		1300	4500	5520	420	1270	1680	2.3	5.9	7.7	3.54	A++	7.47	211
		7	12		2000	3500		1300	5500	6550	420	1500	2470	2.3	6.9	11.3	3.50	A++	7.14	270
		7	18		1860	4640		1300	6500	7740	420	1660	2690	2.3	7.6	12.3	3.62	A++	7.54	302
		9	9		2500	2500		1300	5000	5950	420	1430	2260	2.3	6.6	10.3	3.50	A++	7.55	232
		9	12		2500	3500		1300	6000	7140	420	1650	2670	2.3	7.5	12.2	3.64	A++	7.48	281
		9	18		2270	4530		1380	6800	8090	430	1870	2660	2.3	8.5	12.2	3.64	A++	7.57	314
		12	12		3250	3250		1300	6500	7740	420	1770	2700	2.3	8.0	12.4	3.67	A++	7.56	301
		12	18		2800	4000		1380	6800	8090	430	1880	2670	2.3	8.5	12.2	3.62	A++	7.56	315
	18	18		3400	3400		1380	6800	8090	430	1850	2660	2.3	8.4	12.2	3.68	A++	7.58	314	
	3 Unit	7	7	7	2000	2000	2000	1800	6000	7400	440	1620	2650	2.3	7.4	12.1	3.70	A++	7.62	276
		7	7	9	2000	2000	2500	1800	6500	8000	440	1770	2690	2.3	8.0	12.3	3.67	A++	7.64	298
		7	7	12	1810	1810	3180	1800	6800	8400	440	1850	2700	2.3	8.4	12.4	3.68	A++	7.67	310
		7	7	18	1510	1510	3780	1800	6800	8400	440	1800	2690	2.3	8.1	12.3	3.78	A++	7.69	309
		7	9	9	1860	2320	2320	1800	6500	8000	440	1670	2690	2.3	7.6	12.3	3.90	A++	7.75	293
		7	9	12	1700	2130	2970	1800	6800	8400	440	1840	2690	2.3	8.3	12.3	3.70	A++	7.67	310
		7	9	18	1430	1790	3580	1800	6800	8400	440	1830	2690	2.3	8.3	12.3	3.72	A++	7.68	310
		7	12	12	1520	2640	2640	1800	6800	8400	440	1830	2700	2.3	8.3	12.4	3.72	A++	7.68	310
		7	12	18	1300	2270	3230	1800	6800	8400	440	1830	2700	2.3	8.3	12.4	3.72	A++	7.68	310
		9	9	9	2260	2270	2270	1800	6800	8400	440	1820	2690	2.3	8.3	12.3	3.74	A++	7.68	310
		9	9	12	2000	2000	2800	1800	6800	8400	440	1820	2700	2.3	8.3	12.4	3.74	A++	7.68	310
		9	9	18	1700	1700	3400	1800	6800	8400	440	1810	2690	2.3	8.2	12.3	3.76	A++	7.69	310
		9	12	12	1780	2510	2510	1800	6800	8400	440	1810	2700	2.3	8.2	12.4	3.76	A++	7.69	310
		9	12	18	1550	2160	3090	1800	6800	8400	440	1800	2700	2.3	8.1	12.4	3.78	A++	7.69	309
		12	12	12	2260	2270	2270	1800	6800	8400	440	1800	2710	2.3	8.1	12.4	3.78	A++	7.69	309



4. Combination Table

HEATING

Outdoor unit		A	B	C	Heating Capacity			Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe
					W			W			W			A							
					A	B	C	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX	COP	Class		kW	kWh
AJ068TXJ3KG/EU	2 Unit	7	7		2200	2200		1400	4400	5060	380	1150	1600	1.9	4.9	7.3	3.83	A+	4.25	3.05	1006
		7	9		2200	3300		1400	5500	6330	380	1400	2000	1.9	6.0	9.2	3.93	A+	4.2	4.21	1401
		7	12		2200	4000		1400	6200	7130	380	1590	2300	1.9	6.8	10.5	3.90	A+	4.17	4.52	1517
		7	18		2090	5710		1400	7800	8970	380	1880	2700	1.9	8.5	12.4	4.14	A+	4.26	5.65	1856
		9	9		3300	3300		1400	6600	7590	380	1770	2600	1.9	7.5	11.9	3.73	A+	4.22	4.91	1628
		9	12		3300	4000		1400	7300	8400	380	1870	2600	1.9	8.0	11.9	3.90	A+	4.19	5.09	1699
		9	18		2770	5030		1400	7800	8970	380	1940	2800	1.9	8.7	12.8	4.02	A+	4.23	5.09	1683
		12	12		3900	3900		1400	7800	8970	380	1910	2700	1.9	8.6	12.4	4.08	A+	4.27	5.09	1668
		12	18		3200	4800		1400	8000	9200	380	1990	2800	1.9	9.0	12.8	4.02	A+	4.23	5.09	1683
		18	18		4000	4000		1400	8000	9200	380	1980	2800	1.9	8.9	12.8	4.04	A+	4.28	5.65	1847
	3 Unit	7	7	7	2200	2200	2200	1400	6600	8100	380	1540	2400	1.9	6.6	11.0	4.28	A+	4.24	5.65	1867
		7	7	9	2200	2200	3300	1400	7700	9500	380	1780	2500	1.9	8.1	11.4	4.32	A+	4.24	5.65	1867
		7	7	12	2100	2100	3800	1400	8000	9800	380	1870	2600	1.9	8.5	11.9	4.28	A+	4.26	5.65	1856
		7	7	18	1690	1690	4620	1400	8000	9800	380	1860	2600	1.9	8.4	11.9	4.30	A+	4.26	5.65	1856
		7	9	9	2000	3000	3000	1400	8000	9800	380	1810	2500	1.9	8.2	11.4	4.42	A+	4.32	5.65	1833
		7	9	12	1850	2780	3370	1400	8000	9800	380	1830	2600	1.9	8.3	11.9	4.37	A+	4.24	5.65	1867
		7	9	18	1530	2300	4170	1400	8000	9800	380	1860	2600	1.9	8.4	11.9	4.30	A+	4.24	5.65	1867
		7	12	12	1720	3140	3140	1400	8000	9800	380	1860	2600	1.9	8.4	11.9	4.30	A+	4.24	5.65	1867
		7	12	18	1450	2620	3930	1400	8000	9800	380	1860	2600	1.9	8.4	11.9	4.30	A+	4.24	5.65	1867
		9	9	9	2660	2670	2670	1400	8000	9800	380	1850	2600	1.9	8.4	11.9	4.32	A+	4.24	5.65	1867
		9	9	12	2490	2490	3020	1400	8000	9800	380	1850	2600	1.9	8.4	11.9	4.32	A+	4.26	5.65	1856
		9	9	18	2100	2100	3800	1400	8000	9800	380	1870	2600	1.9	8.5	11.9	4.28	A+	4.26	5.65	1856
		9	12	12	2340	2830	2830	1400	8000	9800	380	1870	2600	1.9	8.5	11.9	4.28	A+	4.24	5.65	1867
		9	12	18	1980	2410	3610	1400	8000	9800	380	1890	2700	1.9	8.6	12.4	4.23	A+	4.24	5.65	1867
		12	12	12	2660	2670	2670	1400	8000	9800	380	1810	2600	1.9	8.2	11.9	4.42	A+	4.32	5.65	1833

NOTE

- 1 EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- 2 The above is the value for connecting with the following indoor units.
 - Wind Free(PRM) : AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK
- 3 You can not connect a single unit.
- 4 Power consumption include indoor unit power.

4. Combination Table

4-5 AJ080TXJ4KG/EU

COOLING

Outdoor unit		A	B	C	D	Cooling Capacity				Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
						W				W			W			A						kWh
						A	B	C	D	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				MIN
AJ080TXJ4KG	2 Unit	7	7			2000	2000			1640	4000	4800	410	1110	1490	1.9	4.9	6.8	3.60	A++	755	185
		7	9			2040	2560			1690	4600	5520	420	1310	1720	1.9	5.8	7.9	3.51	A++	747	216
		7	12			2000	3500			1770	5500	6600	430	1570	2050	2.0	6.9	9.4	3.50	A++	714	270
		7	18			2060	5140			1900	7200	8640	580	2050	2690	2.7	8.9	12.3	3.51	A++	731	345
		7	24			1690	5760			1900	7450	8640	580	2130	2730	2.7	9.3	12.5	3.50	A++	725	359
		9	9			2600	2600			1750	5200	6240	420	1480	2000	1.9	6.5	9.2	3.51	A++	73	249
		9	12			2540	3560			1820	6100	7320	440	1680	2260	2.0	7.4	10.3	3.63	A++	746	286
		9	18			2400	4800			1900	7200	8640	580	2050	2690	2.7	8.9	12.3	3.51	A++	731	345
		9	24			2030	5520			1900	7550	8760	580	2150	2760	2.7	9.4	12.6	3.51	A++	726	364
		12	12			3500	3500			1900	7000	8000	580	2000	2620	2.7	8.7	12.0	3.50	A++	73	336
		12	18			3030	4320			1900	7350	8820	580	2110	2750	2.7	9.2	12.6	3.48	A++	727	354
		12	24			2620	5080			1900	7700	8930	580	2180	2780	2.7	9.5	12.7	3.53	A++	721	377
		18	18			3830	3830			1900	7660	9180	580	2120	2860	2.7	9.2	13.1	3.61	A++	721	372
		18	24			3310	4490			1900	7800	8970	580	2150	2820	2.7	9.4	12.9	3.63	A++	722	378
	3 Unit	7	7	7		2000	2000	2000		1810	6000	7200	440	1620	2310	2.0	6.9	10.6	3.70	A++	762	276
		7	7	9		2030	2030	2540		1870	6600	7920	440	1810	2500	2.0	7.7	11.4	3.65	A++	758	305
		7	7	12		1920	1920	3360		1900	7200	9000	580	2020	2780	2.7	8.6	12.7	3.56	A++	745	338
		7	7	18		1680	1680	4190		1900	7550	9180	580	2130	2730	2.7	9.1	12.5	3.54	A++	775	341
		7	7	24		1480	1480	5040		1900	8000	9300	580	2090	2870	2.7	8.9	13.1	3.83	A++	775	361
		7	9	9		2000	2500	2500		1900	7000	8640	580	1930	2680	2.7	8.2	12.3	3.63	A++	735	348
		7	9	12		1830	2280	3200		1900	7310	9060	580	2030	2690	2.7	8.6	12.3	3.60	A++	775	330
		7	9	18		1610	2010	4030		1900	7650	9250	580	2050	2730	2.7	8.7	12.5	3.73	A++	781	343
		7	9	24		1420	1770	4810		1900	8000	9300	580	2030	2870	2.7	8.7	13.1	3.94	A++	777	360
		7	12	12		1680	2930	2930		1900	7540	9160	580	2070	2730	2.7	8.8	12.5	3.64	A++	778	339
		7	12	18		1500	2630	3750		1900	7880	9300	580	2050	2820	2.7	8.7	12.9	3.84	A++	774	356
		7	18	18		1330	3330	3330		1900	8000	9300	580	2010	2910	2.7	8.6	13.3	3.98	A++	778	360
		9	9	9		2400	2400	2400		1900	7200	9030	580	1950	2640	2.7	8.3	12.1	3.69	A++	777	324
		9	9	12		2180	2180	3060		1900	7420	9130	580	2040	2690	2.7	8.7	12.3	3.64	A++	777	334
		9	9	18		1940	1940	3890		1900	7770	9300	580	1950	2780	2.7	8.3	12.7	3.98	A++	777	350
		9	9	24		1690	1690	4610		1900	8000	9300	580	2000	2910	2.7	8.5	13.3	4.00	A++	779	359
		9	12	12		2010	2820	2820		1900	7650	9230	580	2080	2730	2.7	8.9	12.5	3.68	A++	779	344
		9	12	18		1820	2550	3640		1900	8000	9300	580	2020	2870	2.7	8.6	13.1	3.96	A++	778	360
		12	12	12		2630	2630	2630		1900	7890	9300	580	2120	2820	2.7	9.0	12.9	3.72	A++	771	358
		12	12	18		2330	2330	3330		1900	8000	9300	580	2110	2910	2.7	9.0	13.3	3.79	A++	774	362
	4 Unit	7	7	7	7	1830	1830	1830	1830	1900	7320	9050	580	1800	2690	2.7	8.2	12.3	4.06	A++	767	334
		7	7	7	9	1750	1750	1750	2190	1900	7440	9120	580	1850	2690	2.7	8.4	12.3	4.02	A++	767	340
		7	7	7	12	1610	1610	1610	2820	1900	7650	9220	580	1900	2730	2.7	8.6	12.5	4.03	A++	769	348
		7	7	7	18	1450	1450	1450	3650	1900	8000	9300	580	2000	2870	2.7	9.0	13.1	4.00	A++	77	364
		7	7	9	9	1680	1680	2090	2090	1900	7540	9180	580	1870	2730	2.7	8.5	12.5	4.03	A++	768	344
		7	7	9	12	1550	1550	1940	2720	1900	7760	9280	580	1940	2780	2.7	8.8	12.7	4.00	A++	769	353
		7	7	9	18	1390	1390	1740	3480	1900	8000	9300	580	1970	2870	2.7	8.9	13.1	4.06	A++	772	363
		7	7	12	12	1450	1450	2550	2550	1900	8000	9300	580	1990	2870	2.7	9.0	13.1	4.02	A++	771	363
		7	9	9	9	1610	2010	2010	2010	1900	7650	9250	580	1900	2730	2.7	8.6	12.5	4.03	A++	769	348
		7	9	9	12	1500	1880	1880	2630	1900	7890	9300	580	1960	2820	2.7	8.9	12.9	4.03	A++	77	359
		7	9	9	18	1330	1670	1670	3330	1900	8000	9300	580	1970	2910	2.7	8.9	13.3	4.06	A++	772	363
		7	9	12	12	1400	1740	2430	2430	1900	8000	9300	580	1970	2870	2.7	8.9	13.1	4.06	A++	772	363
		9	9	9	9	1940	1940	1940	1940	1900	7760	9300	580	1940	2780	2.7	8.8	12.7	4.00	A++	769	353
		9	9	9	12	1820	1820	1820	2540	1900	8000	9300	580	1970	2870	2.7	8.9	13.1	4.06	A++	772	363
		9	9	12	12	1670	1670	2330	2330	1900	8000	9300	580	1970	2910	2.7	8.9	13.3	4.06	A++	772	363

4. Combination Table

HEATING

Outdoor unit		A	B	C	D	Heating Capacity				Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design				
						W				W			W			A						kW	kWh			
						A	B	C	D	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX								
AJ080TXJ4KG	2 Unit	7	7			2200	2200			1980	4400	5060	600	1150	1530	2.7	4.9	7.0	3.83	A+	4.25	3.05	1006			
		7	9			2040	3060			2040	5100	5870	610	1290	1700	2.8	5.5	7.8	3.95	A+	4.20	4.21	1401			
		7	12			2130	3870			2110	6000	6900	610	1530	2110	2.8	6.5	9.7	3.92	A+	4.11	4.91	1669			
		7	18			2090	5710			2200	7800	9130	620	1920	2580	2.8	8.2	11.8	4.06	A+	4.18	5.09	1705			
		7	24			1790	6330			2200	8120	9300	620	2000	2600	2.8	8.5	11.9	4.06	A+	4.18	5.2	1742			
		9	9			2900	2900			2100	5800	6670	610	1470	1930	2.8	6.3	8.8	3.94	A+	4.11	4.91	1669			
		9	12			3030	3670			2170	6700	7710	610	1730	2330	2.8	7.4	10.7	3.87	A+	4.11	4.91	1669			
		9	18			2770	5030			2200	7800	9360	620	1920	2600	2.8	8.2	11.9	4.06	A+	4.18	5.09	1705			
		9	24			2480	5870			2200	8350	9600	620	2220	2700	2.8	9.5	12.4	3.94	A+	4.18	5.2	1742			
		12	12			3800	3800			2200	7600	8740	620	1890	2510	2.8	8.1	11.5	4.02	A+	4.18	5.09	1705			
		12	18			3250	4870			2200	8120	9500	620	2000	2650	2.8	8.5	12.1	4.06	A+	4.18	5.09	1705			
		12	24			2860	5590			2200	8450	9700	620	2100	2700	2.8	8.9	12.4	4.02	A+	4.18	5.09	1705			
		18	18			4250	4250			2200	8500	9950	620	2080	2750	2.8	8.9	12.6	4.09	A+	4.10	5.88	2010			
		18	24			3760	4890			2200	8650	9900	620	2110	2800	2.8	9.0	12.8	4.10	A+	4.10	5.88	2010			
	3 Unit	7	7	7		2200	2200	2200		2170	6600	7590	610	1540	2220	2.8	6.6	10.2	4.28	A+	4.14	5.65	1912			
		7	7	9		2090	2090	3120		2200	7300	8400	620	1670	2340	2.8	7.1	10.7	4.37	A+	4.10	5.88	2010			
		7	7	12		2150	2150	3900		2200	8200	9590	620	1950	2570	2.8	8.3	11.8	4.21	A+	4.10	5.88	2010			
		7	7	18		1820	1820	4980		2200	8620	10090	620	2040	2610	2.8	8.7	11.9	4.23	A+	4.10	5.88	2009			
		7	7	24		1580	1580	5590		2200	8750	10500	620	2080	2750	2.8	8.9	12.6	4.21	A+	4.11	5.88	2003			
		7	9	9		2000	3000	3000		2200	8000	9360	620	1930	2500	2.8	8.2	11.4	4.14	A+	4.10	5.88	2010			
		7	9	12		1980	2960	3590		2200	8530	9980	620	2000	2690	2.8	8.5	12.3	4.27	A+	4.10	5.88	2009			
		7	9	18		1660	2490	4530		2200	8680	10150	620	2030	2740	2.8	8.6	12.5	4.28	A+	4.10	5.88	2009			
		7	9	24		1540	2310	5450		2200	9300	10900	620	2150	2820	2.8	9.2	12.9	4.33	A+	4.11	5.88	2003			
		7	12	12		1860	3370	3370		2200	8600	10070	620	2030	2740	2.8	8.6	12.5	4.24	A+	4.10	5.88	2009			
		7	12	18		1580	2870	4300		2200	8750	10500	620	2080	2750	2.8	8.9	12.6	4.21	A+	4.11	5.88	2003			
		7	18	18		1440	3930	3930		2200	9300	10900	620	2150	2820	2.8	9.2	12.9	4.33	A+	4.11	5.88	2003			
		9	9	9		2840	2840	2840		2200	8520	9960	620	1990	2680	2.8	8.5	12.3	4.28	A+	4.10	5.88	2009			
		9	9	12		2670	2670	3250		2200	8590	10050	620	2030	2690	2.8	8.6	12.3	4.23	A+	4.10	5.88	2009			
		9	9	18		2290	2290	4170		2200	8750	10500	620	2080	2740	2.8	8.9	12.5	4.21	A+	4.11	5.88	2003			
		9	9	24		2130	2130	5040		2200	9300	10900	620	2170	2820	2.8	9.2	12.9	4.29	A+	4.11	5.88	2003			
		9	12	12		2520	3070	3070		2200	8660	10130	620	2040	2740	2.8	8.7	12.5	4.24	A+	4.10	5.88	2009			
		9	12	18		2310	2800	4190		2200	9300	10500	620	2130	2750	2.8	9.1	12.6	4.37	A+	4.11	5.88	2003			
		12	12	12		2910	2910	2910		2200	8730	10220	620	2070	2750	2.8	8.8	12.6	4.22	A+	4.11	5.88	2003			
		12	12	18		2660	2660	3980		2200	9300	10900	620	2160	2790	2.8	9.2	12.8	4.31	A+	4.11	5.88	2003			
	4 Unit	7	7	7	7	2130	2130	2130	2130	2200	8520	9970	620	1990	2690	2.8	8.9	12.3	4.28	A+	4.11	5.88	2003			
		7	7	7	9	1910	1910	1910	2850	2200	8580	10040	620	2030	2690	2.8	9.0	12.3	4.23	A+	4.11	5.88	2003			
		7	7	7	12	1800	1800	1800	3250	2200	8650	10120	620	2020	2740	2.8	9.0	12.5	4.28	A+	4.11	5.88	2003			
		7	7	7	18	1620	1620	1620	4440	2200	9300	10900	620	2130	2820	2.8	9.5	12.9	4.37	A+	4.11	5.88	2003			
		7	7	9	9	1730	1730	2590	2590	2200	8640	10100	620	2020	2740	2.8	9.0	12.5	4.28	A+	4.11	5.88	2003			
		7	7	9	12	1640	1640	2460	2970	2200	8710	10190	620	2040	2740	2.8	9.1	12.5	4.27	A+	4.11	5.88	2003			
		7	7	9	18	1490	1490	2240	4080	2200	9300	10900	620	2130	2820	2.8	9.5	12.9	4.37	A+	4.11	5.88	2003			
		7	7	12	12	1560	1560	2830	2830	2200	8780	10270	620	2070	2790	2.8	9.2	12.8	4.24	A+	4.11	5.88	2003			
		7	9	9	9	1580	2370	2370	2370	2200	8690	10170	620	2030	2740	2.8	9.0	12.5	4.28	A+	4.11	5.88	2003			
		7	9	9	12	1510	2260	2260	2730	2200	8760	10250	620	2060	2790	2.8	9.2	12.8	4.25	A+	4.11	5.88	2003			
		7	9	9	18	1390	2070	2070	3770	2200	9300	10900	620	2130	2820	2.8	9.5	12.9	4.37	A+	4.11	5.88	2003			
		7	9	12	12	1520	2260	2760	2760	2200	9300	10900	620	2130	2820	2.8	9.5	12.9	4.37	A+	4.11	5.88	2003			
		9	9	9	9	2190	2190	2190	2190	2200	8760	10240	620	2060	2740	2.8	9.2	12.5	4.25	A+	4.11	5.88	2003			
		9	9	9	12	2210	2210	2210	2670	2200	9300	10900	620	2130	2790	2.8	9.5	12.8	4.37	A+	4.11	5.88	2003			
		9	9	12	12	2100	2100	2550	2550	2200	9300	10900	620	2130	2820	2.8	9.5	12.9	4.37	A+	4.11	5.88	2003			

NOTE

- EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- The above is the value for connecting with the following indoor units.
 - Wind Free(PRM) : AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK
- You can not connect a single unit.
- Power consumption include indoor unit power.

4. Combination Table

4-5 AJ100TXJ5KG/EU

COOLING

Outdoor unit		A	B	C	D	E	Cooling Capacity					Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce
							W					W			W			A						
							A	B	C	D	E	MIN	STD	MAX	MIN	NOM	MAX	MIN	STD	MAX				MIN
AJ100TXJ5KG	2 Unit	7	7				2000	2000				1680	4000	4900	610	1110	1650	2.8	4.7	7.6	3.60	A++	728	192
		7	9				2000	2500				1680	4500	5530	610	1270	1860	2.8	5.4	8.5	3.55	A++	739	213
		7	12				2000	3500				1710	5500	6950	620	1570	2330	2.8	6.7	10.7	3.50	A++	740	260
		7	18				2000	5000				2210	7000	8690	630	1970	2910	2.9	8.4	13.3	3.55	A++	737	332
		7	24				1830	6240				2280	8070	10110	650	2290	3390	3.0	9.8	15.5	3.52	A++	730	387
		9	9				2500	2500				1680	5000	6320	610	1400	2120	2.8	6.0	9.7	3.58	A++	749	234
		9	12				2500	3500				1710	6000	7270	620	1690	2430	2.8	7.2	11.1	3.55	A++	746	282
		9	18				2500	5000				2210	7500	9320	630	2140	3120	2.9	9.1	14.3	3.51	A++	733	358
		9	24				2190	5960				2280	8150	10110	650	2340	3390	3.0	10.0	15.5	3.48	A++	730	391
		12	12				3500	3500				2170	7000	8530	620	1960	2850	2.8	8.4	13.0	3.58	A++	738	332
		12	18				3300	4720				2240	8020	9950	640	2260	3330	2.9	9.6	15.2	3.55	A++	731	386
		12	24				2920	5670				2480	8590	10740	660	2480	3600	3.0	10.6	16.5	3.47	A++	715	420
		18	18				4280	4280				2440	8560	10430	650	2460	3500	3.0	10.5	16.0	3.48	A++	715	419
		18	24				3740	5080				2510	8820	10900	670	2470	3670	3.1	10.5	16.8	3.57	A++	729	423
		24	24				4550	4550				3110	9100	11000	690	2560	3740	3.2	10.9	17.1	3.55	A++	730	436
	3 Unit	7	7	7			2000	2000	2000			1760	6000	7270	640	1660	2460	2.9	7.1	11.3	3.62	A++	748	281
		7	7	9			2000	2000	2500			1760	6500	7900	640	1780	2660	2.9	7.6	12.2	3.65	A++	748	281
		7	7	12			2000	2000	3500			2280	7500	8850	650	2080	2980	3.0	8.9	13.6	3.61	A++	752	349
		7	7	18			1930	1930	4830			2310	8690	10270	660	2500	3450	3.0	10.7	15.8	3.48	A++	791	391
		7	7	24			1660	1660	5650			2550	8970	10430	680	2560	3530	3.1	10.9	16.2	3.51	A++	765	411
		7	9	9			2000	2500	2500			2240	7000	8370	640	1920	2820	2.9	8.2	12.9	3.64	A++	750	326
		7	9	12			2000	2500	3500			2280	8000	9320	650	2230	3130	3.0	9.5	14.3	3.58	A++	777	361
		7	9	18			1850	2310	4620			2310	8780	10270	660	2480	3450	3.0	10.6	15.8	3.54	A++	792	388
		7	9	24			1550	1940	5270			2550	8760	10430	680	2470	3530	3.1	10.5	16.2	3.54	A++	792	387
		7	12	12			1930	3380	3380			2280	8690	10270	650	2500	3440	3.0	10.7	15.7	3.48	A++	791	391
		7	12	18			1700	2980	4250			2510	8930	10430	670	2590	3510	3.1	11.0	16.1	3.45	A++	790	396
		7	12	24			1460	2550	4950			2760	8960	10740	690	2550	3630	3.2	10.9	16.6	3.51	A++	765	410
		7	18	18			1480	3710	3710			2720	8900	10740	680	2540	3630	3.1	10.8	16.6	3.50	A++	792	394
		7	18	24			1340	3360	4560			3150	9260	11000	700	2570	3750	3.2	11.0	17.2	3.61	A++	775	418
		7	24	24			1260	4270	4270			3240	9800	11000	720	2720	3770	3.3	11.6	17.3	3.60	A++	777	442
		9	9	9			2500	2500	2500			2240	7500	8850	640	2080	2970	2.9	8.9	13.6	3.61	A++	752	349
		9	9	12			2500	2500	3500			2280	8500	9950	650	2390	3340	3.0	10.2	15.3	3.55	A++	791	376
		9	9	18			2210	2210	4430			2480	8850	10270	660	2520	3450	3.0	10.7	15.8	3.51	A++	792	391
		9	9	24			1880	1880	5110			2550	8870	10740	680	2530	3630	3.1	10.8	16.6	3.51	A++	792	392
		9	12	12			2310	3230	3230			2280	8770	10270	650	2440	3440	3.0	10.4	15.7	3.59	A++	793	387
		9	12	18			1980	2770	3950			2510	8700	10430	670	2420	3510	3.1	10.3	16.1	3.59	A++	793	384
		9	12	24			1770	2480	4810			2760	9060	10900	690	2570	3690	3.2	11.0	16.9	3.52	A++	766	414
		9	18	18			1800	3600	3600			2720	9000	10900	680	2560	3680	3.1	10.9	16.8	3.52	A++	765	412
		9	18	24			1640	3270	4450			3150	9360	11000	700	2590	3750	3.2	11.0	17.2	3.61	A++	775	423
		9	24	24			1520	4140	4140			3240	9800	11000	720	2660	3770	3.3	11.3	17.3	3.68	A++	779	440
		12	12	12			2980	2980	2980			2480	8940	10430	660	2410	3500	3.0	10.3	16.0	3.71	A++	798	392
		12	12	18			2600	2600	3710			2680	8910	10740	670	2410	3620	3.1	10.3	16.6	3.69	A++	797	391
		12	12	24			2350	2350	4560			3110	9260	11000	690	2540	3740	3.2	10.8	17.1	3.64	A++	775	418
		12	18	18			2390	3410	3410			3110	9210	11000	690	2530	3740	3.2	10.8	17.1	3.64	A++	775	416
		12	18	24			2240	3200	4360			3200	9800	11000	710	2750	3760	3.2	11.7	17.2	3.57	A++	775	442
		12	24	24			2000	3900	3900			3290	9800	11000	730	2750	3780	3.3	11.7	17.3	3.57	A++	775	442
		18	18	18			3260	3270	3270			3150	9800	11000	700	2750	3750	3.2	11.7	17.2	3.57	A++	775	442
		18	18	24			2920	2920	3960			3240	9800	11000	720	2750	3770	3.3	11.7	17.3	3.57	A++	775	442

4. Combination Table

Outdoor unit	A	B	C	D	E	Cooling Capacity					Capacity			Power Consumption			Current			Effic. NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce	
						W					W			W			A							
						A	B	C	D	E	MIN	STD	MAX	MIN	NOM	MAX	MIN	STD	MAX	EER	Class		kWh	
AJ100TXJ5KG	4 Unit	7	7	7	7	2000	2000	2000	2000		2350	8000	9320	670	2170	3160	3.1	9.2	14.5	3.68	A++	7.79	359	
		7	7	7	9	2000	2000	2000	2500		2350	8500	9950	670	2290	3360	3.1	9.8	15.4	3.71	A++	7.95	374	
		7	7	7	12	1850	1850	1850	3230		2380	8780	10270	680	2390	3470	3.1	10.2	15.9	3.68	A++	7.96	386	
		7	7	7	18	1580	1580	1580	3950		2590	8690	10430	690	2330	3540	3.2	9.9	16.2	3.73	A++	7.97	382	
		7	7	7	24	1420	1420	1420	4820		2840	9080	10900	710	2460	3710	3.2	10.5	17.0	3.69	A++	7.71	412	
		7	7	9	9	1930	1930	2420	2420		2350	8700	10270	670	2330	3460	3.1	9.9	15.8	3.73	A++	7.97	382	
		7	7	9	12	1770	1770	2210	3100		2550	8850	10270	680	2420	3470	3.1	10.3	15.9	3.66	A++	7.96	389	
		7	7	9	18	1530	1530	1910	3830		2590	8800	10740	690	2380	3640	3.2	10.1	16.7	3.70	A++	7.97	387	
		7	7	9	24	1380	1380	1720	4680		3200	9160	10900	710	2490	3710	3.2	10.6	17.0	3.68	A++	7.76	413	
		7	7	12	12	1580	1580	2770	2770		2550	8700	10430	680	2280	3530	3.1	9.7	16.2	3.82	A++	8.00	381	
		7	7	12	18	1440	1440	2520	3600		2800	9000	10900	700	2420	3700	3.2	10.3	16.9	3.72	A++	7.71	409	
		7	7	12	24	1310	1310	2290	4450		3240	9360	11000	720	2530	3770	3.3	10.8	17.3	3.70	A++	7.78	421	
		7	7	18	18	1330	1330	3320	3320		3200	9300	11000	710	2510	3760	3.2	10.7	17.2	3.71	A++	7.78	419	
		7	7	18	24	1240	1240	3100	4220		3290	9800	11000	730	2620	3780	3.3	11.2	17.3	3.74	A++	7.81	439	
		7	9	9	9	1850	2310	2310	2310		2350	8780	10270	670	2290	3460	3.1	9.8	15.8	3.84	A++	8.01	384	
		7	9	9	12	1700	2130	2130	2980		2550	8940	10430	680	2370	3520	3.1	10.1	16.1	3.78	A++	8.00	391	
		7	9	9	18	1480	1850	1850	3700		2760	8880	10740	690	2340	3640	3.2	10.0	16.7	3.79	A++	8.00	389	
		7	9	9	24	1340	1680	1680	4560		3200	9260	11000	710	2420	3760	3.2	10.3	17.2	3.82	A++	7.80	415	
		7	9	12	12	1530	1910	2680	2680		2550	8800	10740	680	2290	3630	3.1	9.8	16.6	3.84	A++	8.01	385	
		7	9	12	18	1400	1750	2450	3500		3150	9100	10900	700	2410	3700	3.2	10.3	16.9	3.78	A++	7.78	409	
		7	9	12	24	1280	1600	2240	4350		3240	9470	11000	720	2530	3770	3.3	10.8	17.3	3.75	A++	7.79	425	
		7	9	18	18	1300	1620	3240	3240		3200	9400	11000	710	2510	3760	3.2	10.7	17.2	3.75	A++	7.79	422	
		7	9	18	24	1200	1500	3010	4090		3290	9800	11000	730	2630	3780	3.3	11.2	17.3	3.73	A++	7.80	440	
		7	12	12	12	1440	2520	2520	2520		2760	9000	10900	690	2340	3690	3.2	10.0	16.9	3.84	A++	8.02	393	
		7	12	12	18	1330	2330	2330	3330		3150	9320	11000	700	2470	3750	3.2	10.5	17.2	3.78	A++	7.79	418	
		7	12	12	24	1240	2170	2170	4220		3240	9800	11000	720	2630	3770	3.3	11.2	17.3	3.73	A++	7.80	440	
		7	12	18	18	1270	2210	3160	3160		3240	9800	11000	720	2630	3770	3.3	11.2	17.3	3.73	A++	7.80	440	
		7	12	18	24	1140	1980	2830	3850		3330	9800	11000	740	2630	3790	3.4	11.2	17.3	3.73	A++	7.80	440	
		7	18	18	18	1160	2880	2880	2880		3290	9800	11000	730	2630	3780	3.3	11.2	17.3	3.73	A++	7.80	440	
		9	9	9	9	2210	2210	2210	2210		2510	8840	10270	670	2330	3460	3.1	9.9	15.8	3.80	A++	8.00	387	
		9	9	9	12	1980	1980	1980	2770		2550	8710	10430	680	2290	3520	3.1	9.8	16.1	3.80	A++	7.99	381	
		9	9	9	18	1800	1800	1800	3600		2760	9000	10900	690	2390	3690	3.2	10.2	16.9	3.76	A++	7.72	408	
		9	9	9	24	1640	1640	1640	4460		3200	9380	11000	710	2520	3760	3.2	10.7	17.2	3.72	A++	7.78	422	
		9	9	12	12	1850	1850	2600	2600		2720	8900	10740	680	2350	3630	3.1	10.0	16.6	3.78	A++	8.00	390	
		9	9	12	18	1700	1700	2390	3410		3150	9200	11000	700	2430	3750	3.2	10.4	17.2	3.78	A++	7.79	413	
		9	9	12	24	1600	1600	2240	4360		3240	9800	11000	720	2630	3770	3.3	11.2	17.3	3.73	A++	7.80	440	
		9	9	18	18	1630	1630	3270	3270		3200	9800	11000	710	2630	3760	3.2	11.2	17.2	3.73	A++	7.80	440	
		9	9	18	24	1460	1460	2920	3960		3290	9800	11000	730	2630	3780	3.3	11.2	17.3	3.73	A++	7.80	440	
		9	12	12	12	1750	2450	2450	2450		3110	9100	10900	690	2430	3690	3.2	10.4	16.9	3.74	A++	8.00	398	
		9	12	12	18	1620	2270	2270	3240		3150	9400	11000	700	2520	3750	3.2	10.7	17.2	3.73	A++	7.79	423	
		9	12	12	24	1510	2100	2100	4090		3240	9800	11000	720	2630	3770	3.3	11.2	17.3	3.73	A++	7.80	440	
		9	12	18	18	1540	2140	3060	3060		3240	9800	11000	720	2630	3770	3.3	11.2	17.3	3.73	A++	7.80	440	
		12	12	12	12	2330	2330	2330	2330		3110	9320	11000	690	2830	3740	3.2	12.1	17.1	3.29	A++	7.79	419	
		12	12	12	18	2210	2210	2210	3170		3200	9800	11000	710	2630	3760	3.2	11.2	17.2	3.73	A++	7.80	440	
		12	12	12	24	1980	1980	1980	3860		3290	9800	11000	730	2630	3780	3.3	11.2	17.3	3.73	A++	7.80	440	
		12	12	18	18	2020	2020	2880	2880		3240	9800	11000	720	2630	3770	3.3	11.2	17.3	3.73	A++	7.80	440	

4. Combination Table

Outdoor unit	A	B	C	D	E	Cooling Capacity					Capacity			Power Consumption			Current			Effic.NOM. Cooling. At 35°C/27°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SEER	Qce	
						W					W			W			A							
						A	B	C	D	E	MIN	STD	MAX	MIN	NOM	MAX	MIN	STD	MAX	EER	Class		kWh	
AJ100TXJ5KG	5 Unit	7	7	7	7	7	1900	1900	1900	1900	2630	9500	10270	700	2570	3490	3.2	11.5	16.0	3.69	A++	778	427	
		7	7	7	7	9	1820	1820	1820	1820	2270	2630	9550	10430	700	2600	3550	3.2	11.6	16.2	3.68	A++	778	430
		7	7	7	7	12	1680	1680	1680	1680	2940	2660	9660	10740	710	2630	3650	3.2	11.7	16.7	3.68	A++	778	434
		7	7	7	7	18	1540	1540	1540	1540	3840	3240	10000	10900	720	2750	3720	3.3	12.2	17.0	3.64	A++	779	449
		7	7	7	7	24	1350	1350	1350	1350	4600	3330	10000	11000	740	2750	3790	3.4	12.2	17.3	3.64	A++	779	449
		7	7	7	9	9	1750	1750	1750	2180	2180	2630	9610	10430	700	2610	3550	3.2	11.6	16.2	3.68	A++	778	432
		7	7	7	9	12	1620	1620	1620	2020	2830	2840	9710	10740	710	2670	3650	3.2	11.9	16.7	3.64	A++	777	437
		7	7	7	9	18	1480	1480	1480	1860	3700	3240	10000	11000	720	2730	3770	3.3	12.1	17.3	3.66	A++	779	449
		7	7	7	9	24	1310	1310	1310	1630	4440	3330	10000	11000	740	2730	3790	3.4	12.1	17.3	3.66	A++	779	449
		7	7	7	12	12	1540	1540	1540	1540	2690	3200	10000	10900	710	2750	3710	3.2	12.2	17.0	3.64	A++	779	449
		7	7	7	12	18	1380	1380	1380	2410	3450	3290	10000	11000	730	2760	3780	3.3	12.3	17.3	3.62	A++	778	450
		7	7	7	12	24	1230	1230	1230	2150	4160	3380	10000	11000	750	2760	3800	3.4	12.3	17.4	3.62	A++	778	450
		7	7	7	18	18	1240	1240	1240	3140	3140	3330	10000	11000	740	2760	3790	3.4	12.3	17.3	3.62	A++	778	450
		7	7	9	9	9	1680	1680	2100	2100	2100	2630	9660	10740	700	2630	3650	3.2	11.7	16.7	3.68	A++	778	434
		7	7	9	9	12	1600	1600	2000	2000	2800	2840	10000	10900	710	2750	3710	3.2	12.2	17.0	3.64	A++	779	449
		7	7	9	9	18	1430	1430	1790	1790	3560	3240	10000	11000	720	2760	3770	3.3	12.3	17.3	3.62	A++	778	450
		7	7	9	9	24	1270	1270	1580	1580	4300	3330	10000	11000	740	2760	3790	3.4	12.3	17.3	3.62	A++	778	450
		7	7	9	12	12	1480	1480	1860	2590	2590	3200	10000	11000	710	2750	3760	3.2	12.2	17.2	3.64	A++	779	449
		7	7	9	12	18	1330	1330	1680	2330	3330	3290	10000	11000	730	2780	3780	3.3	12.3	17.3	3.60	A++	778	450
		7	7	9	12	24	1190	1190	1490	2080	4050	3380	10000	11000	750	2780	3800	3.4	12.3	17.4	3.60	A++	778	450
		7	7	9	18	18	1210	1210	1520	3030	3030	3330	10000	11000	740	2780	3790	3.4	12.3	17.3	3.60	A++	778	450
		7	7	12	12	12	1370	1370	2420	2420	2420	3240	10000	11000	720	2750	3770	3.3	12.2	17.3	3.64	A++	779	449
		7	7	12	18	18	1250	1250	2190	2190	3120	3290	10000	11000	730	2760	3780	3.3	12.3	17.3	3.62	A++	778	450
		7	9	9	9	9	1620	2020	2020	2020	2800	9700	10740	700	2610	3650	3.2	11.6	16.7	3.71	A++	779	436	
		7	9	9	9	12	1550	1920	1920	1920	2690	3200	10000	10900	710	2750	3710	3.2	12.2	17.0	3.64	A++	779	449
		7	9	9	9	18	1390	1720	1720	1720	3450	3240	10000	11000	720	2760	3770	3.3	12.3	17.3	3.62	A++	778	450
		7	9	9	9	24	1240	1530	1530	1530	4170	3330	10000	11000	740	2760	3790	3.4	12.3	17.3	3.62	A++	778	450
		7	9	9	12	12	1440	1790	1790	2490	2490	3200	10000	11000	710	2720	3760	3.2	12.1	17.2	3.68	A++	778	434
		7	9	9	12	18	1290	1610	1610	2260	3230	3290	10000	11000	730	2760	3780	3.3	12.3	17.3	3.62	A++	778	450
		7	9	9	12	24	1160	1450	1450	2020	3920	3380	10000	11000	750	2760	3800	3.4	12.3	17.4	3.62	A++	778	450
		7	9	9	18	18	1180	1470	1470	2940	2940	3330	10000	11000	740	2780	3790	3.4	12.3	17.3	3.60	A++	778	450
		7	9	12	12	12	1340	1670	2330	2330	2330	3240	10000	11000	720	2750	3770	3.3	12.2	17.3	3.64	A++	779	449
		7	9	12	18	18	1210	1520	2120	2120	3030	3290	10000	11000	730	2750	3780	3.3	12.2	17.3	3.64	A++	779	449
		7	12	12	12	12	1240	2190	2190	2190	2190	3240	10000	11000	720	2750	3770	3.3	12.2	17.3	3.64	A++	779	449
		9	9	9	9	9	2000	2000	2000	2000	3000	10000	11000	700	2750	3700	3.2	12.2	16.9	3.64	A++	779	449	
		9	9	9	9	12	1850	1850	1850	1850	2600	3200	10000	11000	710	2750	3760	3.2	12.2	17.2	3.64	A++	779	449
		9	9	9	9	18	1670	1670	1670	1670	3320	3240	10000	11000	720	2760	3770	3.3	12.3	17.3	3.62	A++	778	450
		9	9	9	9	24	1490	1490	1490	1490	4040	3330	10000	11000	740	2760	3790	3.4	12.3	17.3	3.62	A++	778	450
		9	9	9	12	12	1720	1720	1720	2420	2420	3200	10000	11000	710	2750	3760	3.2	12.2	17.2	3.64	A++	779	449
		9	9	9	12	18	1560	1560	1560	2190	3130	3290	10000	11000	730	2760	3780	3.3	12.3	17.3	3.62	A++	778	450
		9	9	12	12	12	1610	1610	2260	2260	2260	3240	10000	11000	720	2750	3770	3.3	12.2	17.3	3.64	A++	779	449
		9	9	12	18	18	1470	1470	2060	2060	2940	3290	10000	11000	730	2760	3780	3.3	12.3	17.3	3.62	A++	778	450
		9	12	12	12	12	1520	2120	2120	2120	2120	3240	10000	11000	720	2750	3770	3.3	12.2	17.3	3.64	A++	779	449



4. Combination Table

HEATING

Outdoor unit		A	B	C	D	E	Heating Capacity					Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design			
							W					W			W			A						kW	kWh		
							A	B	C	D	E	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX		Class					
AJ100TXJ5KG	2 Unit	7	7				2200	2200				1240	4400	5530	460	1070	1520	2.1	4.6	7.0	4.10	A+	4.16	3.05	1028		
		7	9				2200	3300				1240	5500	6790	460	1360	1850	2.1	5.8	8.5	4.05	A+	4.15	4.21	1418		
		7	12				2200	4000				1270	6200	7580	470	1490	2060	2.2	6.3	9.4	4.15	A+	4.19	4.91	1638		
		7	18				2200	6000				1300	8200	10110	480	2010	2750	2.2	8.6	12.6	4.08	A+	4.09	5.88	2010		
		7	24				2200	7800				1500	10000	12480	500	2490	3390	2.3	10.6	15.5	4.01	A+	4.03	7.70	2671		
		9	9				3300	3300				1240	6600	8220	460	1630	2230	2.1	6.9	10.2	4.06	A+	4.19	4.91	1638		
		9	12				3300	4000				1270	7300	9010	470	1810	2440	2.2	7.7	11.2	4.04	A+	4.19	4.91	1638		
		9	18				3300	6000				1300	9300	11690	480	2320	3160	2.2	9.9	14.5	4.01	A+	4.03	7.70	2671		
		9	24				3150	7450				1500	10600	13110	500	2640	3560	2.3	11.2	16.3	4.02	A+	4.03	7.70	2671		
		12	12				4000	4000				1270	8000	9800	470	1940	2650	2.2	8.3	12.1	4.13	A+	4.19	4.91	1638		
		12	18				4000	6000				1470	10000	12320	490	2490	3330	2.2	10.6	15.2	4.01	A+	4.03	7.70	2671		
		12	24				3590	7010				1530	10600	13110	510	2670	3560	2.3	11.4	16.3	3.97	A+	4.03	7.70	2671		
		18	18				5300	5300				1650	10600	13110	500	2660	3560	2.3	11.3	16.3	3.99	A+	4.03	7.70	2671		
		18	24				4610	5990				1820	10600	13110	520	2640	3580	2.4	11.2	16.4	4.02	A+	4.03	7.70	2671		
		24	24				5300	5300				2160	10600	12960	540	2640	3560	2.5	11.2	16.3	4.02	A+	4.03	7.70	2671		
	3 Unit	7	7	7			2200	2200	2200			1320	6600	7580	490	1590	2090	2.2	6.8	9.6	4.14	A+	4.18	5.65	1893		
		7	7	9			2200	2200	3300			1320	7700	9010	490	1850	2460	2.2	7.9	11.3	4.17	A+	4.18	5.65	1893		
		7	7	12			2200	2200	4000			1350	8400	9800	500	2030	2680	2.3	8.6	12.3	4.14	A+	4.23	5.88	1939		
		7	7	18			2050	2050	5590			1530	9690	12170	510	2380	3320	2.3	10.1	15.2	4.08	A+	4.25	7.91	2607		
		7	7	24			1780	1780	6300			1750	9860	12170	530	2420	3340	2.4	10.3	15.3	4.08	A+	4.25	7.91	2607		
		7	9	9			2200	3300	3300			1320	8800	10740	490	2110	2920	2.2	9.0	13.4	4.18	A+	4.23	5.88	1939		
		7	9	12			2200	3300	4000			1350	9500	11380	500	2350	3090	2.3	10.0	14.1	4.05	A+	4.25	7.91	2607		
		7	9	18			1870	2810	5110			1530	9790	11850	510	2400	3230	2.3	10.2	14.8	4.08	A+	4.25	7.91	2607		
		7	9	24			1650	2470	5850			1860	9970	12170	530	2440	3340	2.4	10.4	15.3	4.08	A+	4.25	7.91	2607		
		7	12	12			2090	3790	3790			1500	9670	12170	500	2370	3310	2.3	10.1	15.1	4.08	A+	4.25	7.91	2607		
		7	12	18			1780	3230	4850			1720	9860	12170	520	2420	3320	2.4	10.3	15.2	4.07	A+	4.25	7.91	2607		
		7	12	24			1580	2870	5590			1890	10040	12320	540	2440	3380	2.5	10.4	15.5	4.11	A+	4.25	7.91	2607		
		7	18	18			1560	4250	4250			1860	10060	12320	530	2450	3380	2.4	10.4	15.5	4.10	A+	4.25	7.91	2607		
		7	18	24			1490	4050	5270			2200	10810	12800	550	2610	3520	2.5	11.1	16.1	4.14	A+	4.25	7.91	2607		
		7	24	24			1360	4820	4820			2280	11000	12960	570	2640	3590	2.6	11.2	16.4	4.16	A+	4.25	7.91	2607		
		9	9	9			3210	3210	3210			1470	9630	11850	490	2360	3210	2.2	10.1	14.7	4.08	A+	4.23	5.88	1939		
		9	9	12			3020	3020	3660			1500	9700	11530	500	2340	3140	2.3	10.0	14.4	4.15	A+	4.25	7.91	2607		
		9	9	18			2590	2590	4710			1680	9890	12320	510	2410	3360	2.3	10.3	15.4	4.11	A+	4.25	7.91	2607		
		9	9	24			2440	2440	5770			1860	10650	12480	530	2620	3420	2.4	11.2	15.7	4.07	A+	4.25	7.91	2607		
		9	12	12			2850	3460	3460			1500	9770	11850	500	2340	3220	2.3	10.0	14.7	4.17	A+	4.25	7.91	2607		
		9	12	18			2470	3000	4500			1820	9970	12170	520	2410	3320	2.4	10.3	15.2	4.14	A+	4.25	7.91	2607		
		9	12	24			2340	2840	5540			1890	10720	12480	540	2650	3430	2.5	11.3	15.7	4.05	A+	4.25	7.91	2607		
		9	18	18			2320	4210	4210			1860	10740	12480	530	2650	3420	2.4	11.3	15.7	4.05	A+	4.25	7.91	2607		
		9	18	24			2120	3860	5020			2200	11000	12960	550	2700	3570	2.5	11.5	16.3	4.08	A+	4.25	7.91	2607		
		9	24	24			1920	4540	4540			2280	11000	13110	570	2290	3630	2.6	9.8	16.6	4.80	A+	4.25	7.91	2607		
		12	12	12			3280	3280	3280			1680	9840	12170	510	2350	3310	2.3	10.0	15.1	4.18	A+	4.25	7.91	2607		
		12	12	18			2870	2870	4300			1820	10040	12320	520	2440	3370	2.4	10.4	15.4	4.11	A+	4.25	7.91	2607		
		12	12	24			2730	2730	5330			2160	10790	12800	540	2610	3510	2.5	11.1	16.1	4.13	A+	4.25	7.91	2607		
		12	18	18			2700	4050	4050			2160	10800	12800	540	2610	3510	2.5	11.1	16.1	4.14	A+	4.25	7.91	2607		
		12	18	24			2470	3710	4820			2240	11000	12960	560	2660	3570	2.6	11.3	16.3	4.13	A+	4.25	7.91	2607		
		12	24	24			2240	4380	4380			2320	11000	13430	580	2660	3720	2.7	11.3	17.0	4.13	A+	4.25	7.91	2607		
		18	18	18			3660	3670	3670			2200	11000	12960	550	2660	3570	2.5	11.3	16.3	4.13	A+	4.25	7.91	2607		
		18	18	24			3330	3330	4340			2280	11000	13430	570	2660	3710	2.6	11.3	17.0	4.13	A+	4.25	7.91	2607		

4. Combination Table

Outdoor unit	A	B	C	D	E	Heating Capacity					Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design	Qhe			
						W					W			W			A										
						A	B	C	D	E	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				kW	kWh			
AJ100TXJ5KG	4 Unit	7	7	7	7	2200	2200	2200	2200		1400	8800	9800	520	2110	2700	2.4	9.0	12.4	4.18	A+	4.25	791	2607			
		7	7	7	9	2140	2140	2140	3210		1560	9630	11380	520	2320	3120	2.4	9.9	14.3	4.15	A+	4.25	791	2607			
		7	7	7	12	2010	2010	2010	3660		1590	9690	12170	530	2330	3330	2.4	9.9	15.2	4.15	A+	4.25	791	2607			
		7	7	7	18	1730	1730	1730	4710		1780	9900	12170	540	2410	3350	2.5	10.3	15.3	4.11	A+	4.25	791	2607			
		7	7	7	24	1630	1630	1630	5770		1960	10660	12320	560	2620	3410	2.6	11.2	15.6	4.07	A+	4.25	791	2607			
		7	7	9	9	1950	1950	2920	2920		1560	9740	11530	520	2350	3160	2.4	10.0	14.5	4.15	A+	4.25	791	2607			
		7	7	9	12	1840	1840	2760	3350		1590	9790	11850	530	2390	3250	2.4	10.2	14.9	4.09	A+	4.25	791	2607			
		7	7	9	18	1610	1610	2410	4380		1890	10010	12170	540	2440	3350	2.5	10.4	15.3	4.11	A+	4.25	791	2607			
		7	7	9	24	1530	1530	2290	5410		1960	10760	12480	560	2620	3450	2.6	11.2	15.8	4.10	A+	4.25	791	2607			
		7	7	12	12	1750	1750	3190	3190		1750	9880	12170	530	2360	3340	2.4	10.1	15.3	4.19	A+	4.25	791	2607			
		7	7	12	18	1630	1630	2960	4440		1930	10660	12320	550	2610	3390	2.5	11.1	15.5	4.09	A+	4.25	791	2607			
		7	7	12	24	1470	1470	2670	5210		2280	10820	12800	570	2630	3540	2.6	11.2	16.2	4.11	A+	4.25	791	2607			
		7	7	18	18	1460	1460	3970	3970		2240	10860	12800	560	2640	3530	2.6	11.2	16.2	4.11	A+	4.25	791	2607			
		7	7	18	24	1330	1330	3630	4710		2320	11000	12960	580	2680	3600	2.7	11.4	16.5	4.10	A+	4.25	791	2607			
		7	9	9	9	1790	2690	2690	2690		1720	9860	12170	520	2390	3330	2.4	10.2	15.2	4.13	A+	4.25	791	2607			
		7	9	9	12	1710	2560	2560	3100		1750	9930	12320	530	2410	3370	2.4	10.3	15.4	4.12	A+	4.25	791	2607			
		7	9	9	18	1590	2380	2380	4330		1890	10680	12480	540	2620	3430	2.5	11.2	15.7	4.08	A+	4.25	791	2607			
		7	9	9	24	1440	2160	2160	5100		2240	10860	12960	560	2670	3580	2.6	11.4	16.4	4.07	A+	4.25	791	2607			
		7	9	12	12	1630	2440	2960	2960		1860	9990	12170	530	2440	3340	2.4	10.4	15.3	4.10	A+	4.25	791	2607			
		7	9	12	18	1530	2290	2780	4170		1930	10770	12480	550	2640	3440	2.5	11.2	15.7	4.08	A+	4.25	791	2607			
		7	9	12	24	1400	2100	2540	4960		2280	11000	12960	570	2680	3580	2.6	11.4	16.4	4.11	A+	4.25	791	2607			
		7	9	18	18	1390	2070	3770	3770		2240	11000	12960	560	2680	3580	2.6	11.4	16.4	4.11	A+	4.25	791	2607			
		7	9	18	24	1250	1880	3420	4450		2320	11000	13110	580	2680	3640	2.7	11.4	16.7	4.11	A+	4.25	791	2607			
		7	12	12	12	1560	2830	2830	2830		1890	10050	12320	540	2420	3380	2.5	10.3	15.5	4.15	A+	4.25	791	2607			
		7	12	12	18	1470	2670	2670	4010		2200	10820	12800	550	2650	3520	2.5	11.3	16.1	4.08	A+	4.25	791	2607			
		7	12	12	24	1350	2440	2440	4770		2280	11000	12960	570	2680	3590	2.6	11.4	16.4	4.11	A+	4.25	791	2607			
		7	12	18	18	1330	2410	3630	3630		2280	11000	12960	570	2680	3580	2.6	11.4	16.4	4.11	A+	4.25	791	2607			
		7	12	18	24	1210	2200	3300	4290		2360	11000	13430	590	2680	3730	2.7	11.4	17.1	4.11	A+	4.25	791	2607			
		7	18	18	18	1190	3270	3270	3270		2320	11000	13430	580	2680	3720	2.7	11.4	17.0	4.11	A+	4.25	791	2607			
		9	9	9	9	2490	2490	2490	2490		1820	9960	12480	520	2310	3410	2.4	9.8	15.6	4.32	A+	4.32	791	2564			
		9	9	9	12	2380	2380	2380	2880		1860	10020	12320	530	2340	3370	2.4	10.0	15.4	4.28	A+	4.25	791	2607			
		9	9	9	18	2240	2240	2240	4080		2160	10800	12800	540	2610	3510	2.5	11.1	16.1	4.14	A+	4.25	791	2607			
		9	9	9	24	2050	2050	2050	4850		2240	11000	12960	560	2680	3580	2.6	11.4	16.4	4.11	A+	4.25	791	2607			
		9	9	12	12	2410	2410	2920	2920		1860	10660	12480	530	2510	3420	2.4	10.7	15.7	4.24	A+	4.25	791	2607			
		9	9	12	18	2160	2160	2620	3930		2200	10870	12960	550	2630	3560	2.5	11.2	16.3	4.13	A+	4.25	791	2607			
		9	9	12	24	1970	1970	2400	4660		2280	11000	13110	570	2680	3620	2.6	11.4	16.6	4.11	A+	4.25	791	2607			
		9	9	18	18	1950	1950	3550	3550		2240	11000	13110	560	2680	3620	2.6	11.4	16.6	4.11	A+	4.25	791	2607			
		9	9	18	24	1780	1780	3240	4200		2320	11000	13590	580	2680	3760	2.7	11.4	17.2	4.11	A+	4.25	791	2607			
		9	12	12	12	2320	2810	2810	2810		1890	10750	12480	540	2600	3430	2.5	11.1	15.7	4.13	A+	4.25	791	2607			
		9	12	12	18	2100	2540	2540	3820		2200	11000	12960	550	2680	3570	2.5	11.4	16.3	4.11	A+	4.25	791	2607			
		9	12	12	24	1910	2300	2300	4490		2280	11000	13110	570	2680	3630	2.6	11.4	16.6	4.11	A+	4.25	791	2607			
		9	12	18	18	1880	2280	3420	3420		2280	11000	13110	570	2680	3620	2.6	11.4	16.6	4.11	A+	4.25	791	2607			
		12	12	12	12	2700	2700	2700	2700		2160	10800	12800	540	2610	3510	2.5	11.1	16.1	4.14	A+	4.25	791	2607			
		12	12	12	18	2440	2440	2440	3680		2240	11000	12960	560	2680	3570	2.6	11.4	16.3	4.11	A+	4.25	791	2607			
		12	12	12	24	2220	2220	2220	4340		2320	11000	13430	580	2680	3720	2.7	11.4	17.0	4.11	A+	4.25	791	2607			
		12	12	18	18	2200	2200	3300	3300		2280	11000	13430	570	2680	3710	2.6	11.4	17.0	4.11	A+	4.25	791	2607			

4. Combination Table

Outdoor unit		A	B	C	D	E	Heating Capacity					Capacity			Power Consumption			Current			Effic. NOM. Heating. At 7°C/20°C	SEASONAL EFFICIENCY (ACCORDING EN14825)	SCOP	P design		Qhe						
							W					W			W			A														
							A	B	C	D	E	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX												
AJ100TXJ5KG	5 Unit	7	7	7	7	7	2200	2200	2200	2200	2200	1650	11000	13110	550	2560	3610	2.5	11.7	16.5	4.30	A+	4.25	791	2607							
		7	7	7	7	9	2080	2080	2080	2080	3120	1820	11440	12960	550	2670	3570	2.5	12.2	16.3	4.28	A+	4.25	791	2607							
		7	7	7	7	12	1990	1990	1990	1990	3620	1850	11580	13110	560	2720	3610	2.6	12.4	16.5	4.26	A+	4.25	791	2607							
		7	7	7	7	18	1710	1710	1710	1710	4660	2000	11500	13430	570	2700	3710	2.6	12.3	17.0	4.26	A+	4.25	791	2607							
		7	7	7	7	24	1580	1580	1580	1580	5610	2360	11930	13750	590	2810	3810	2.7	12.8	17.4	4.24	A+	4.25	791	2607							
		7	7	7	9	9	1950	1950	1950	2930	2930	1930	11710	13430	550	2750	3690	2.5	12.5	16.9	4.26	A+	4.25	791	2607							
		7	7	7	9	12	1880	1880	1880	2820	3420	1960	11880	13110	560	2800	3610	2.6	12.7	16.5	4.24	A+	4.25	791	2607							
		7	7	7	9	18	1630	1630	1630	2440	4450	2280	11780	13590	570	2790	3750	2.6	12.7	17.2	4.22	A+	4.25	791	2607							
		7	7	7	9	24	1490	1490	1490	2240	5290	2360	12000	13900	590	2820	3860	2.7	12.8	17.7	4.26	A+	4.25	791	2607							
		7	7	7	12	12	1730	1730	1730	3140	3140	1960	11470	13430	560	2680	3700	2.6	12.2	16.9	4.28	A+	4.25	791	2607							
		7	7	7	12	18	1580	1580	1580	2880	4320	2320	11940	13750	580	2830	3800	2.7	12.9	17.4	4.22	A+	4.25	791	2607							
		7	7	7	12	24	1430	1430	1430	2620	5090	2400	12000	14000	600	2830	3940	2.7	12.9	18.0	4.24	A+	4.25	791	2607							
		7	7	7	18	18	1420	1420	1420	3870	3870	2360	12000	14000	590	2830	3940	2.7	12.9	18.0	4.24	A+	4.25	791	2607							
		7	7	9	9	9	1840	1840	2760	2760	2760	1930	11960	13430	550	2810	3690	2.5	12.8	16.9	4.26	A+	4.25	791	2607							
		7	7	9	9	12	1690	1690	2540	2540	3080	1960	11540	13590	560	2700	3740	2.6	12.3	17.1	4.28	A+	4.25	791	2607							
		7	7	9	9	18	1550	1550	2330	2330	4240	2280	12000	13900	570	2820	3840	2.6	12.8	17.6	4.26	A+	4.25	791	2607							
		7	7	9	9	24	1400	1400	2110	2110	4980	2360	12000	14000	590	2820	3940	2.7	12.8	18.0	4.26	A+	4.25	791	2607							
		7	7	9	12	12	1640	1640	2470	2990	2990	2240	11730	13590	560	2750	3740	2.6	12.5	17.1	4.26	A+	4.25	791	2607							
		7	7	9	12	18	1490	1490	2240	2710	4070	2320	12000	13900	580	2840	3840	2.7	12.9	17.6	4.22	A+	4.25	791	2607							
		7	7	9	12	24	1350	1350	2040	2460	4800	2400	12000	14000	600	2840	3940	2.7	12.9	18.0	4.22	A+	4.25	791	2607							
		7	7	9	18	18	1340	1340	2020	3650	3650	2360	12000	14000	590	2840	3940	2.7	12.9	18.0	4.22	A+	4.25	791	2607							
		7	7	12	12	12	1600	1600	2900	2900	2900	2280	11900	13750	570	2780	3790	2.6	12.6	17.3	4.28	A+	4.25	791	2607							
		7	7	12	12	18	1430	1430	2610	2610	3920	2320	12000	14000	580	2840	3930	2.7	12.9	18.0	4.22	A+	4.25	791	2607							
		7	9	9	9	9	1670	2500	2500	2500	2500	1930	11670	13590	550	2720	3730	2.5	12.4	17.1	4.29	A+	4.25	791	2607							
		7	9	9	9	12	1620	2420	2420	2420	2940	2240	11820	13750	560	2760	3780	2.6	12.6	17.3	4.28	A+	4.25	791	2607							
		7	9	9	9	18	1460	2190	2190	2190	3970	2280	12000	14000	570	2830	3920	2.6	12.9	17.9	4.24	A+	4.25	791	2607							
		7	9	9	9	24	1330	1990	1990	1990	4700	2360	12000	14000	590	2830	3940	2.7	12.9	18.0	4.24	A+	4.25	791	2607							
		7	9	9	12	12	1570	2350	2360	2860	2860	2240	12000	13900	560	2820	3830	2.6	12.8	17.5	4.26	A+	4.25	791	2607							
		7	9	9	12	18	1400	2110	2110	2550	3830	2320	12000	14000	580	2870	3920	2.7	13.0	17.9	4.18	A+	4.25	791	2607							
		7	9	9	12	24	1290	1920	1920	2330	4540	2400	12000	14000	600	2870	3940	2.7	13.0	18.0	4.18	A+	4.25	791	2607							
		7	9	9	18	18	1280	1900	1900	3460	3460	2360	12000	14000	590	2860	3940	2.7	13.0	18.0	4.20	A+	4.25	791	2607							
		7	9	12	12	12	1520	2260	2740	2740	2740	2280	12000	13900	570	2850	3830	2.6	12.9	17.5	4.21	A+	4.25	791	2607							
		7	9	12	12	18	1360	2030	2460	2460	3690	2320	12000	14000	580	2850	3930	2.7	12.9	18.0	4.21	A+	4.25	791	2607							
		7	12	12	12	12	1440	2640	2640	2640	2640	2280	12000	14000	570	2830	3920	2.6	12.9	17.9	4.24	A+	4.25	791	2607							
		9	9	9	9	9	2400	2400	2400	2400	2400	3400	12000	14000	550	2820	3900	2.5	12.8	17.8	4.26	A+	4.25	791	2607							
		9	9	9	9	12	2300	2300	2300	2300	2800	2240	12000	13900	560	2820	3820	2.6	12.8	17.5	4.25	A+	4.25	791	2607							
		9	9	9	9	18	2060	2060	2060	2060	3760	2280	12000	14000	570	2840	3920	2.6	12.9	17.9	4.23	A+	4.25	791	2607							
		9	9	9	9	24	1890	1890	1890	1890	4440	2360	12000	14000	590	2840	3940	2.7	12.9	18.0	4.23	A+	4.25	791	2607							
		9	9	9	12	12	2210	2210	2210	2680	2690	2240	12000	14000	560	2840	3910	2.6	12.9	17.9	4.23	A+	4.25	791	2607							
		9	9	9	12	18	1990	1990	1990	2410	3620	2320	12000	14000	580	2830	3920	2.7	12.9	17.9	4.24	A+	4.25	791	2607							
		9	9	12	12	12	2130	2130	2580	2580	2580	2280	12000	14000	570	2840	3910	2.6	12.9	17.9	4.23	A+	4.25	791	2607							
		9	9	12	12	18	1920	1920	2330	2330	3500	3400	12000	14000	580	2850	3930	2.7	12.9	18.0	4.21	A+	4.25	791	2607							
		9	12	12	12	12	2040	2490	2490	2490	2490	2280	12000	14000	570	2850	3920	2.6	12.9	17.9	4.21	A+	4.25	791	2607							

NOTE

- 1 EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalog.
- 2 The above is the value for connecting with the following indoor units.
 - Wind Free(PRM) : AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK
- 3 You can not connect a single unit.
- 4 Power consumption include indoor unit power.